

MOUSE 2

The CliqTec MOUSE 2 is a fully silicone-sealed computer mouse engineered for medical, laboratory, and hygienically critical environments. Its smooth, seamless surface enables easy disinfection and full washability without compromising ergonomic comfort or usability.



Perfect Scroll Options

Precise control via a responsive embedded scroll area. Two programmable buttons are assigned to scroll up and down by default (one line per click).



CleanLock

Ensure data sanity by deactivating the MOUSE 2 with CleanLock to prevent all input while disinfecting – no accidental clicks, no need to disconnect cables.



Sustainable Charging

A USB-C rechargeable lithium-ion battery enables sustainable wireless use, reducing disposable battery waste in daily medical workflows.



Side Buttons

The first medical-grade mouse built for more than just pointing. Additional buttons bring workflow shortcuts to medical workspaces, saving time with every click.



Easy Cleaning

Fully washable and disinfectable for optimal hygiene. Built to withstand frequent cleaning with common medical disinfectants without degrading over time.



Ergonomic Design

An ergonomic body shape supports the palm of the hand and reduces wrist strain, ensuring lasting comfort during extended working sessions.



IP68 Waterproof

Fully sealed with an IP68 rating, the mouse is protected against dust, dirt, and liquid ingress – making it suitable for even the most demanding environments.

Specifications

MOUSE 2

Product features

Protection	IP68
Sensor type	Laser
Max. resolution (dpi)	1200 dpi
Connection	Wired (USB, cable length: 1.8 m) Wireless (USB RF Dongle, 2.4 GHz)
Colour	White
Compatibility	All operating systems supporting USB mice
Buttons and controls	2 primary buttons + 2 programmable side buttons (default: back/forward), on/off button, embedded scroll area

Technical specifications

Weight	135 g (wired) / 140 g (wireless)
Dimensions (D × W × H)	123 × 65.5 × 42 mm
Storage temperature	- 20 °C to + 70 °C
Operating temperature	0 °C to + 50 °C
Input voltage range	5V (DC) ± 5 %
Max. current consumption	20 mA
Battery	Li-ion, rechargeable via USB-C (wireless model)
Approval and compliance	CE, FCC
Warranty	24 months



Cliq Technology GmbH
 Absberggasse 27/7.3
 1100 Vienna
 Austria

www.cliqtec.eu
office@cliqtec.eu
 +43 650 680 33 94